

SOLID SUBSTRATE -
SLOPE 1/4:12, MIN.

SHIM AS REQ'D.

CHIMNEY CHASE NOTE:
MAINTAIN MINIMUM
CLEARANCE
OF COMBUSTIBLE
MATERIALS
PER CHIMNEY
MANUFACTURER'S
RECOMMENDATIONS

METAL CHIMNEY CAP (PER PLAN)

ROOFING UNDERLAYMENT

9" WIDE SAF OR WRB STRIP
LAP OVER WRB AT WALL -
SEE NOTES A-1 AND A-3

1X OR 2X BLOCKING AS REQUIRED

3/4" STUCCO KEY
OPTION: USE WOOD STOP
OR J-MOLD OVER SAF

2X TRIM

1" MIN. LAP OVER
TOP OF STONE

DIMENSION TO CLEAR
TOP OF STONE

CULTURED STONE®

MORTAR JOINT (WHERE USED)

MORTAR SETTING BED

MORTAR SCRATCH COAT -
SEE NOTE E

LATH - SEE NOTE F

WRB - SEE NOTE A-1

SHEATHING

1-B CHIMNEY CHASE CAP WITH WOOD TRIM
1.21 SCALE: 3"=1'-0"

COPYRIGHT 2005 Owens Corning

detail is set to display properly using
Architxt.shx font

OC IB 1-21
issued 05/15/2006